




TYPE 1 SPEAKER CABLES: FLAT SERIES



FLAT SPEAKER CABLE - SOLID CONDUCTOR HYPERLITZ

Overall: 2 x 16 AWG (1.23 mm²)

- 2 x 20 AWG Solid **Long-Grain Copper** (LGC) Conductors
- 2 x 18 AWG Solid **LGC** Conductors
- Dark Gray or White PVC Jacket

- (A) Multiple Strands interact electrically and mechanically, causing irritation and one-note bass boom.
- (B) "Oxygen-Free" Copper is Oxygen-Reduced, but is not selected for low distortion.
- (C) High-Inductance Geometry smears sound, reduces information.
- ① Solid Conductors eliminate harshness and confusion due to strand interaction.
- ② Long-Grain Copper means fewer impurities, less grain junctions, lower distortion.
- ③ Low-Inductance Geometry preserves time information, preserving dynamics and clarity.

TERMINATION DIRECTIONS: The 4 conductors of Type 1 can be easily separated and then stripped individually. Take care not to cut the conductors when stripping off ½" (12mm) of PVC jacket. Please follow the color code indicated by the 2 color stripes.

Attach the 2 color-striped conductors to a Black (-) AudioQuest CF-Spade or CF-BFA/Banana connector. AQ CF connector packs include an Allen-key tool for tightening the 2 set-screws. Tighter is better. Attach the 2 un-striped conductors to a Red (+) connector.

If your speaker or amplifier has a screw-terminal or a binding post, you can insert the stripped ends of Type 1 directly. Then, screw down the connection. Tighter is better for preventing corrosion of the connection.

NOT INCLUDED - SOLD SEPARATELY



CF-BFA/BANANA



CF-SPADE



ALLEN KEY