



5085DL / 5055DL SERIES

Clipsal's new Dynamic Labelling Technology™ has been incorporated into the of Ulti and Neo range of C-Bus wall switches. This enables C-Bus installers to electronically label switches according to the requirements of the user and easily change labelling via software as required.

C-Bus Dynamic Labelling Technology™ switches incorporate a backlit 64 x 128 pixel LCD screen. This LCD screen is capable of displaying editable LCD text or bitmap labels, plus function indicators such as bar-graphs.

The units have eight programmable buttons for C-Bus Group/Scene control over two pages, with a Scroll button to toggle between these pages. Text, sliders and bitmaps can be defined in the C-Bus Toolkit software and downloaded to the unit via a C-Bus network.

The units connect directly to C-Bus via the Cat-5 twisted pair network and are powered via this connection. In the event of power failure, non-volatile memory retains all programmed information relating to each unit's operating state.

Dynamic Labelling Technology™ switches are fully compatible with all existing C-Bus units, such as C-Bus wall switches, touch screens and dimmers, and can be used to replace existing C-Bus switches, as well as being included in new C-Bus installations.

C-Bus wall switches with Dynamic Labelling Technology™ can control any combination of C-Bus output devices, including C-Bus Relays and Dimmers. Each button is capable of being programmed to achieve various functions, including toggle-switches, dimmers, timers or many other customisable options.

clipsal.com/cis

Key Features

- Editable LCD Labels with Dynamic Graphic Displays called Function Indicators, which can be optionally enabled/disabled
- LCD labelling for each button
- Eight buttons for C-Bus group/scene over two pages (four buttons per page)
- Page/scroll button
- Each can be programmed as on/off, dimming, time or scene control
- 64 x 128 pixel screen
- Up to 8 languages supported
- Downloadable bitmaps per group address or scene
- Dimmable white LED backlighting for the LCD
- Dimmable blue LED on each button
- Ignore first button press option
- Fallback to page 1 option
- Time clock display
- Available in Ulti and Neo styles
- Programmed via C-Bus Toolkit software
- Nightlight on all buttons or just 5th button
- LCD feedback under Learn Mode
- Scene dimming

Product Specifications

C-Bus Supply Voltage	15 - 36V d.c.
Current Drawn	22mA
AC Input Impedance	50k @ 1kHz
Maximum Number of units on a C-Bus Network	50 units
Control Functions	Load switching, dimming, timing, scene control
Storage Temperature Range	-10° - 60°C
Operating Temperature Range	0° - 45°C
Operating Humidity Range	-10 - 95% R.H.
C-Bus Input Terminals	0.2 - 1.5mm2 (24-16AWG)

Product Range

5085DL,GF	Ulti Saturn Glass, rectangular style C-Bus switch, incorporating Dynamic Labelling Technology™, 5 buttons, White*, Learn Enabled
5055DL, GB	Neo, rectangular style C-Bus switch, incorporating Dynamic Labelling Technology™, 5 buttons, Battleship Grey and Brushed Aluminum, Learn Enabled

*Also available in Black, Mid-Brown and Cream.

C-Bus® is a registered trademark of Clipsal Australia Pty Ltd.

C-Bus2™ is a trademark of Clipsal Australia Pty Ltd.

Product of
Clipsal Integrated Systems Pty Ltd
 Member of Clipsal Australia Holdings Group
 ABN 15 089 444 931

Head Office
 12 Park Terrace, Bowden
 South Australia 5007
 PO Box 103 Hindmarsh,
 South Australia 5007

Telephone (08) 8440 0500
 International +61 8 8440 0500

Facsimile (08) 8346 0845
 International +61 8 8346 0845

Internet www.clipsal.com/cis
 E-Mail cis@clipsal.com.au

CIS Technical Support Hotline
 1300 722 247

International Enquiries

International Sales and Marketing
 Telephone +61 8 8269 0587
 Facsimile +61 8 8340 7350
 E-Mail export@clipsal.com.au

New Zealand
 Clipsal Industries (NZ) Ltd
 Telephone +64 9 576 3403

Malaysia
 Clipsal Integrated Systems (M) Sdn Bhd
 Telephone +60 3 7665 3555

Singapore
 Clipsal Singapore Pte Ltd
 Telephone +65 6415 3211
 Telephone +65 6415 3232

China
 Clipsal China Limited
 Telephone +86 755 8237 5959

Greece
 Schneider Electric AE
 Telephone +30 69 4646 3200

Hong Kong
 Clipsal Integrated Systems (HK) Limited
 Telephone +852 2487 0261

India
 Schneider Electric India Pvt Ltd
 Telephone +91 11 5159 0000

Indonesia
 PT Clipsal Graha Nusa
 Telephone +62 21 630 6430

Korea
 Clipsal Korea Co. Ltd
 Telephone +822 549 5550

Pakistan
 Clipsal Pakistan (Pvt) Ltd
 Telephone +92 21 506 7278

Philippines
 Clipsal Philippines Inc.
 Telephone +632 683 0275-78

South Africa
 Clipsal South Africa (Pty) Ltd
 Telephone +27 11 314 5200

Taiwan
 Clipsal (Taiwan) Co Ltd
 Telephone +886 2 2558 3456

Thailand
 Clipsal Thailand Ltd
 Telephone +66 2 952 5338
 Telephone +66 2 952 5342

United Arab Emirates
 Clipsal Middle East
 Telephone +971 6 5570 777

United Kingdom
 Clipsal Integrated Systems
 C/o Schneider Electric
 Telephone +44 870 608 8 608

Vietnam
 Clipsal - VTEC
 Telephone +848 856 3002



© Clipsal Integrated Systems Pty Ltd 2005.
 Created in Australia 2005. All rights reserved.
 O/N 10113b June 05/01