

C-Bus Single Zone Thermostat



5070THB Series

The C-Bus Single Zone Thermostat is a wall-mounted thermostat with an easy to use interface. The applications for this product include Hotel Rooms and smaller residential C-Bus installations (eg apartments).

From the user's perspective, the unit provides the following functionality:

- Allows the user to manually set the temperature for the air conditioning system
- Allows the user to select the mode of air conditioning, i.e. Heating, Cooling, Ventilation
- Provides a method of customising the operation the unit.

The unit allows manual fan speed control (where the controlled HVAC plant allows for this). This can be enabled or disabled using a configuration parameter during commissioning.

The unit incorporates a 'Setback' or 'Economy Mode' feature which allows the unit to operate with a wider than normal temperature range around a Setpoint. This is usually used when the home or building is unoccupied. Setback allows energy saving, whilst maintaining a degree of comfort.

The Setback feature is enabled or disabled via a C-Bus Lighting Group Address.

All thermostat control parameters are accessible via C-Bus, from the C-Bus Toolkit software. The unit responds to C-Bus HVAC application messages and broadcasts the displayed temperature on C-Bus to enable other C-Bus devices to be able react to this information (eg, C-Bus Colour Touch Screen or Pascal Automation Controller).

The thermostat has a 2 year warranty.

clipsal.com/cis

Product of Clipsal Australia Pty. Ltd.

A member of the Schneider Electric Group.

Head Office

12 Park Terrace, Bowden
 South Australia 5007
 PO Box 103 Hindmarsh
 South Australia 5007

Telephone +61 8 8345 9500
 Facsimile +61 8 8346 0845
 Internet www.clipsal.com/cis
 E-Mail cis@clipsal.com.au

CIS Technical Support Hotline:
 1300 722 247

Customer Service Enquiries:
1300 2025 25

National Customer Service Facsimile:
1300 2025 56

International Enquiries**International Sales and Marketing**

Telephone +61 8 8269 0587
 Facsimile +61 8 8340 7350
 E-Mail export@clipsal.com.au

New Zealand

Clipsal Industries (NZ) Ltd
 Telephone +64 9 576 3403

Malaysia

Clipsal Integrated Systems (M) Sdn Bhd
 Telephone +60 3 7665 3555

Singapore

Clipsal Integrated Systems Pte Ltd
 Telephone +65 6415 3232/3233

China

Clipsal China Limited
 Telephone +86 755 8237 5959

Greece

Schneider Electric AE
 Telephone +30 69 4646 3200

Hong Kong

Clipsal Integrated Systems (HK) Limited
 Telephone +852 2487 0261

India

Schneider Electric India Pvt Ltd
 Telephone +91 11 5159 0000

Indonesia

PT Clipsal Graha Nusa
 Telephone +62 21 630 6430

Korea

Clipsal Korea Co. Ltd
 Telephone +82 549 5550

Pakistan

Clipsal Pakistan (Pvt) Ltd
 Telephone +92 21 506 7278

Philippines

Clipsal Philippines Inc.
 Telephone +632 683 0275-78

South Africa

Clipsal South Africa (Pty) Ltd
 Telephone +27 11 314 5200

Taiwan

Clipsal (Taiwan) Co Ltd
 Telephone +886 2 2558 3456

Thailand

Clipsal Thailand Ltd
 Telephone +66 2 952 5338-42

United Arab Emirates

Clipsal Middle East
 Telephone +971 6 5570 777

United Kingdom

Clipsal Integrated Systems
 C/o Schneider Electric
 Telephone +44 870 608 8 608

Vietnam

Clipsal - VTEC
 Telephone +848 856 3002



Clipsal Australia Pty Ltd reserves the right to change specifications, modify designs and discontinue items without incurring obligation and whilst every effort is made to ensure that descriptions, specifications and other information in this catalogue are correct, no warranty is given in respect thereof and the company shall not be liable for any error therein.

© Clipsal Australia Pty Ltd.

The identified trademarks and copyrights are the property of Clipsal Australia Pty Ltd unless otherwise noted.

Electrical Features:

Temperature Sensor	An on-board sensor is used for temperature measurement. The accuracy of the sensor is $\pm 0.5^{\circ}\text{C}$, with a 0.5°C resolution. The temperature set-point may be set from 10°C to 30°C . The unit is able to display temperatures from -10°C to $+37^{\circ}\text{C}$
On/Off Button	Pressing the on/off button in the off state causes the unit to turn on and enter cool, heat or fan mode, dependant on which was last used. Switching the unit off via the on/off switch causes the connected A/C unit to switch off
Mode Button	The mode button allows the user to select between Heating, Cooling and Fan only operation. The current mode is indicated by icons on the integral LCD. If heater plant is not programmed as enabled (via the unit set-up by the installer) the icon does not appear when the Mode button options are cycled thru by the user
Operating Current	The unit draws 40mA at nominal C-Bus operating voltage
Operating Voltage	The unit operates from nominal C-Bus operating voltage of 15-36V DC.
On-board Relays	The unit with integral relays includes 5 relays rated at 2A @ 24V AC (used for "RWG" HVAC plant control)
LCD Backlight	The LCD includes white LED backlighting
Beeper/Buzzer	To provide audible feedback confirmation of a button press to the user, the unit is capable of emitting a 'Beep' and a 'Buzz'. This feedback is optional, with a parameter set in the C-Bus Toolkit GUI

HVAC Control Unit software parameters:

Selection of single/multi stage compressor operation	If the C-Bus HVAC application message indicates that high cooling/heating is required, and the control of the unit has these options enabled, then multi-stage operation and/or auxiliary heating can be enabled
Minimum output cycle time	This sets the time between HVAC equipment turning off and turning back on again. This allows the HVAC equipment time to release pressure in the gas lines before it restarts
Power-on Delay	A delay of 30 seconds from power on to control relays becoming activated is incorporated. This is to protect the compressor from short cycling in the event of a short power outage
Minimum on time	This sets a minimum time that the HVAC equipment is on. This stops the HVAC equipment from running in short bursts
LCD temperature display	The LCD can display temperature in $^{\circ}\text{C}$ or $^{\circ}\text{F}$