

C-Bus® Indoor PIR Occupancy Detector



5751L Series

The C-Bus® Indoor PIR Occupancy Detector is a C-Bus® input unit used to detect movement by sensing natural thermal radiation emitted from any moving body. When movement is detected, the unit issues commands over the C-Bus® network to control C-Bus® output devices. The sensor is suitable for controlling lighting in homes, apartments, offices, corridors, conference rooms, etc.

The sensor incorporates the C-Bus® 'Learn Mode' feature. Learn mode allows the units to be programmed without the need for a PC connected to the system. Alternatively, the units can be programmed via a PC using the installation software.

The sensor has a detection field that covers an area up to 8.5 metres from the unit, with a field of view of 90°. The unit features a 'lenseless' design with 12 overlapping zones forming a continuous detection field. Therefore uniform sensitivity is achieved across the whole of the detection field with no dead zones. This feature allows for wall or ceiling mounting of the sensor.

The sensor is capable of controlling up to four C-Bus® 'Group Addresses', with each being controlled for a different period if required.

An added feature is that each sensor includes an ambient light level sensor (Sunset Switch) feature, which automatically turns lights on when the ambient light level falls below the threshold level (at sunset), and then turns the lights off again at sunrise. Alternatively, the lights can be programmed to automatically turn off at a set time after sunset.

A light emitting diode (LED) on the sensor head can be programmed to turn on when movement is detected. This enables easy positioning and commissioning of the sensor.

The unit initiates a regular status report, which compares the status of all input and output units within the same C-Bus® 'Application Address'. If a state disagreement exists between the output units and the input units the C-Bus® Indoor PIR Occupancy Detector will change its internal state to suit the output.

clipsal.com/cis

5751L Series C-Bus® Indoor PIR Occupancy Detector

- Capable of controlling up to four C-Bus® 'Group Addresses', with each being controlled for a different period if required
- Incorporates an ambient light level sensor which acts as a Sunset Switch to control the status of the load
- A light emitting diode (LED) on the sensor head can be programmed to turn on when movement is detected, via the installation software, enabling easy positioning and commissioning of the sensor
- Time-out variation from 1 second to 18 hours, 12 minutes and 15 seconds, is set via the installation software
- Light sensitivity variation from one lux to full sunlight is set via an adjustment screw located on the sensor unit
- The detection field that covers an area up to 8.5 metres from the unit, with a field of view of 90°
- Lens less design with 12 overlapping zones forming a continuous detection field
- An electrostatic and electromagnetic shield around the sensor elements reduces false triggering from radio frequency interference (RFI)
- Utilizes high performance pyroelectric ceramic sensors with excellent signal to noise ratio
- An optical bandpass filter minimises unwanted light and heat sources triggering the circuitry
- Dual element detectors minimise false triggering from rapid environmental temperature changes
- Refer to 5751L Installation Instruction for location and mounting details
- Available in Australian and export version
- Wall or ceiling mounted
- Designed to meet Australian and European standards for EMC Compliance and Safety
- Configured via either the C-Bus® Installation Software or via the C-Bus® Learn Enabled feature
- An inbuilt non-volatile memory retains programmed information relating to the current operating status of the unit in the event of a power failure
- Communication with other C-Bus® devices and the C-Bus® supply voltage is obtained via a single C-Bus® twisted pair cable
- Initiates a regular status report, which compares the status of all input and output units within the same C-Bus® 'Application Address'.

Product of Clipsal Australia Pty. Ltd.

A member of the Schneider Electric Group.

Head Office

12 Park Terrace, Bowden
South Australia 5007
PO Box 103 Hindmarsh
South Australia 5007

Telephone +61 8 8345 9500
Facsimile +61 8 8346 0845
Internet www.clipsal.com/cis
E-Mail cis@clipsal.com.au

CIS Technical Support Hotline:
1300 722 247

Customer Service Enquiries:
1300 2025 25

National Customer Service Facsimile:
1300 2025 56

International Enquiries

International Sales and Marketing

Telephone +61 8 8269 0587
Facsimile +61 8 8340 7350
E-Mail export@clipsal.com.au

New Zealand

Clipsal Industries (NZ) Ltd
Telephone +64 9 576 3403

Malaysia

Clipsal Integrated Systems (M) Sdn Bhd
Telephone +60 3 7665 3555

Singapore

Clipsal Integrated Systems Pte Ltd
Telephone +65 6415 3232/3233

China

Clipsal China Limited
Telephone +86 755 8237 5959

Greece

Schneider Electric AE
Telephone +30 69 4646 3200

Hong Kong

Clipsal Integrated Systems (HK) Limited
Telephone +852 2487 0261

India

Schneider Electric India Pvt Ltd
Telephone +91 11 5159 0000

Indonesia

PT Clipsal Graha Nusa
Telephone +62 21 630 6430

Korea

Clipsal Korea Co. Ltd
Telephone +82 549 5550

Pakistan

Clipsal Pakistan (Pvt) Ltd
Telephone +92 21 506 7278

Philippines

Clipsal Philippines Inc.
Telephone +632 683 0275-78

South Africa

Clipsal South Africa (Pty) Ltd
Telephone +27 11 314 5200

Taiwan

Clipsal (Taiwan) Co Ltd
Telephone +886 2 2558 3456

Thailand

Clipsal Thailand Ltd
Telephone +66 2 952 5338-42

United Arab Emirates

Clipsal Middle East
Telephone +971 6 5570 777

United Kingdom

Clipsal Integrated Systems
C/o Schneider Electric
Telephone +44 870 608 8 608

Vietnam

Clipsal - VTEC
Telephone +848 856 3002



Clipsal Australia Pty Ltd reserves the right to change specifications, modify designs and discontinue items without incurring obligation and whilst every effort is made to ensure that descriptions, specifications and other information in this catalogue are correct, no warranty is given in respect thereof and the company shall not be liable for any error therein.

© Clipsal Australia Pty Ltd.

The identified trademarks and copyrights are the property of Clipsal Australia Pty Ltd unless otherwise noted.