

# Dual Relay Module

The Dual Channel Relay, is a heavy duty, mechanically latched, DIN rail mounted relay and is rated at 20 Amps continuous use. The relay can withstand high in-rush currents and is suitable for incandescent, high intensity discharge lamps and fluorescent loads.

The relay module features mechanical on/off control for manual operation.




The dual channel relay must be used in conjunction with the 5504RDP series of relay driver products.



5002RL20

## TECHNICAL INFORMATION

Catalogue Number	<b>5002RL20</b>
Line Supply Voltage	<b>220-240VAC</b>
Supply Frequency	<b>47-53Hz and 57-63Hz</b>
Load Rating per Channel	<b>20A AC3</b>
Contact Type	<b>Voltage free, normally open, mechanically latched</b>
Switch Operations	<b>Greater than 60,000 operations</b>
In-Rush Current	<b>120A (20msec)</b>
Compatible Loads	<b>Resistive, inductive, incandescent and fluorescent</b>
Load Termination	<b>2 x 1.5mm<sup>2</sup> or 1 x 2.5mm<sup>2</sup></b>
Dimensions	<b>4M (M = 17.5mm)</b>
Operating Temperature Range	<b>0° C to 45° C</b>
Operating Humidity Range	<b>0 - 95% RH, non-condensing</b>
Compliance	<b>RCM, CE</b>



CATALOGUE NUMBER	DESCRIPTION
5002RL20	Dual Relay, 20A