

# C-Bus 2-Channel DALI Interface DIN Rail Series

## C-Bus<sup>2</sup>

**CLIPSAL**<sup>®</sup>  
INTEGRATED SYSTEMS



5502DAL

The 5502DAL C-Bus DALI Interface unit is a C-Bus system support device designed to provide an isolated communications path between a C-Bus Network and two DALI Networks. For ease of installation the unit is DIN rail mounted, measuring 4M wide (1M = 17.5 +0.5/-0.0 mm).

The DALI Interface provides two-way communication, i.e. selected C-Bus messages are routed to an appropriate DALI Network, and DALI lighting messages are routed to the C-Bus Network.

The DALI Interface constantly monitors both DALI Networks. It is capable of detecting and reporting faulty lamps in fluorescent ballasts or failed DALI units to C-Bus.

Each DALI Network can have up to 64 addressable DALI devices, such as fluorescent ballasts and low voltage transformers. The DALI Interface does not have its own DALI addresses, i.e. it is transparent and is not "visible" for other DALI devices.

The DALI Interface product incorporates a C-Bus PC Interface Module for communications to the C-Bus Network. Programming of the C-Bus side of the Network Interface can be done in the same manner as programming a standard PC Interface.

Like all the other units that make up a C-Bus system, the C-Bus DALI Interface units are Australian designed, developed and manufactured by Clipsal Integrated Systems Pty Ltd.

[clipsal.com/cis](http://clipsal.com/cis)

**CLIPSAL**

IBS Intelligent Building Series™

## 5502DAL C-Bus DALI Interface Module



- Provides an isolated communications path between a C-Bus Network and two DALI Networks.
- DIN rail mounted, measuring 4M wide (1M = 17.5 +0.5/-0.0 mm).
- Provides two-way communication, i.e. selected C-Bus messages are routed to an appropriate DALI Network, and DALI lightning messages are routed to the C-Bus Network.
- Constantly monitors both DALI Networks.
- Capable of detecting and reporting to C-Bus faulty lamps in fluorescent ballasts or failed DALI units.
- Incorporates a C-Bus PC Interface Module for communications to the C-Bus Network.
- Programming of the C-Bus side of the Network Interface can be done in the same manner as programming a standard PC Interface.
- In normal operation, the unit draws 32mA from the C-Bus Network.
- Contains a pre-programmed C-Bus to DALI and DALI to C-Bus addressing structure.
- Consumes 32mA from the C-Bus network during normal operation.
- C-Bus connections via 2 x RJ45 connectors, allowing similar units to be quickly looped together.
- Capable of generating a C-Bus clock signal and providing a C-Bus network burden. Selectable through the C-Bus Installation software.
- Incorporates a C-Bus and Unit indicator, showing the status of the C-Bus Network and the status of the individual unit.
- Incorporates an onboard non-volatile memory, which is used to store the operating state of the unit in the case of a power loss.
- Capable of being programmed via the installation software without the need for a mains connection.
- A maximum of 50 units may be connected to a single C-Bus network.
- Configured via the C-Bus Installation Software or the Learn Enabled Features.
- Supplied with a 300mm C-Bus Category 5 patch lead complete with pre-terminated RJ45 connectors.
- The output terminals accommodate 2 x 1.5mm<sup>2</sup> or 1 x 2.5mm<sup>2</sup> cable.
- EMC Compliant to meet the requirements for marking with the CE and C-Tick marks.
- Dimensions: W=72mm, H=85mm, D=65mm.
- Weight: 130g.

*Note: Clipsal Integrated Systems Pty Ltd does not manufacture DALI units, power supplies, commissioning software or any other product or service associated with DALI aside from the DALI Interface itself. Check individual DALI component requirements.*

### Clipsal Integrated Systems Pty Ltd

ABN 15 089 444 931

#### Head Office

12 Park Terrace, Bowden, South Australia 5007

Telephone (08) 8269 0560

International +61 8 8269 0560

Facsimile (08) 8346 0845

International +61 8 8346 0845

E-Mail [cis@clipsal.com.au](mailto:cis@clipsal.com.au)

Internet [clipsal.com/cis](http://clipsal.com/cis)

#### International Enquiries

##### Head Office Export Department

Telephone +61 8 8269 0587

Facsimile +61 8 8340 7350

E-Mail [export@clipsal.com.au](mailto:export@clipsal.com.au)

#### New Zealand

Clipsal Industries (NZ) Ltd (Auckland)

Telephone +64 9 576 3403

#### Malaysia

Clipsal Integrated Systems (M) Sdn Bhd

Telephone +60 3 7665 3555

#### Singapore

Clipsal Integrated Systems Pte Ltd

Telephone +65 266 1998

#### Hong Kong

Clipsal Integrated Systems (HK) Ltd

Telephone +852 2 487 0261

#### China

Clipsal China Ltd

Telephone +86 755 246 1122

#### Taiwan

Clipsal (Taiwan) Co Ltd

Telephone +886 2 2558 3456

#### Thailand

Clipsal Thailand Ltd

Telephone +66 2 952 5338

#### South Africa

Clipsal South Africa (Pty) Ltd

Telephone +27 11 314 5200

#### United Kingdom

Clipsal Ltd (UK)

Telephone +44 1494 521 111

#### Greece

Clipsal Hellas S.A.

Telephone +30 1 0993 9165

