

C-Bus®

CLIPSAL®

LIVING ELECTRICAL

C-Bus® 4 Channel Analogue Output, DIN Rail Series



L5504AMP Series

The L5504AMP Series Analogue Output unit provides analogue output voltages in the range 0-10Vdc, which can be used as the control signals for various peripheral devices including electronically dimmable fluorescent lighting ballasts. For ease of installation they are DIN rail mounted, measuring 4 DIN modules wide.

The L5504AMP Series Analogue Output unit comprises of 0-10Vdc output controlled by instructions from the C-Bus® Network. The unit is capable of sinking or sourcing current as appropriate for the connected load. Each channel may drive multiple loads, depending on the load current requirements.

The units include the C-Bus® Learn Mode feature. This allows the units to be programmed without the need for a PC connected to the system. Alternatively, units can be programmed via a computer and the C-Bus® Installation software.

Local toggle buttons are included to allow individual channels to be toggled at each unit, as well as via C-Bus® commands. Remote ON and OFF facilities are available, permitting all channels to be turned ON or OFF without C-Bus® network communication.

clipsal.com/cis

CLIPSAL
 **C-Bus**
Control and Management System

L5504AMP Series C-Bus® Analogue Output

- 0-10Vdc output, can be used as control signals for various peripheral devices including electronically dimmable fluorescent lighting ballasts. Controlled by instructions from the C-Bus® Network
- DIN rail mounted, measuring 4 DIN modules wide
- Capable of sinking or sourcing current as appropriate for the connected load. Each channel may drive multiple loads, depending on the load current requirements
- Incorporates the C-Bus® Learn Mode feature
- Does not consume any current from the C-Bus® network during normal operation
- C-Bus® connections via 2 x RJ45 connectors, allowing similar units to be quickly looped together
- Capable of generating a C-Bus® clock signal and providing a C-Bus® network burden. Selectable through the C-Bus® Installation software
- Local toggle buttons allow individual channels to be toggled at each unit, as well as via C-Bus® commands
- Remote override facilities are available, permitting all channels to be turned ON or OFF without C-Bus® network communication
- Incorporates a C-Bus® and Unit indicator, showing the status of the C-Bus® Network and the status of the individual unit
- Incorporates an onboard non-volatile memory, which is used to store the operating state of the unit in case of power loss
- Draws 22mA from the C-Bus® Network regardless if connected to the mains supply. Does not source any current to the C-Bus® Network
- Capable of being programmed via the installation software without the need for a mains connection
- Output Voltage Range: 0 (± 0.5) to 10 (± 0.5) V.d.c.
- Output Rating - Sourcing: 2.5mA (i.e. minimum of 4k)
- Output Rating - Sinking: 15mA at $V_{out} = 0V$, 8mA at $V_{out} = 10V$, i.e. $I = 15 - (0.7 * V_{out})mA$
- Quiescent Power: 10 Watts
- A maximum of 50 units may be connected to a single C-Bus® network
- Configured via the C-Bus® Installation Software or the Learn Enabled Features
- Supplied with a 300mm C-Bus® Category 5 patch lead complete with pre-terminated RJ45 connectors.
- The output terminals accommodate 2 x 1.5mm² or 1 x 2.5mm² cable.
- EMC Compliant to meet the requirements for marking with the CE and RCM marks
- Dimensions: W=72mm, H=85mm, D=65mm
- Weight: 245g.

Product of Clipsal Australia Pty. Ltd.

A member of the Schneider Electric Group.

Head Office

12 Park Terrace, Bowden
South Australia 5007
PO Box 103 Hindmarsh
South Australia 5007

Telephone +61 8 8345 9500
Facsimile +61 8 8346 0845
Internet www.clipsal.com/cis
E-Mail cis@clipsal.com.au

CIS Technical Support Hotline:

1300 722 247

Customer Service Enquiries:

1300 2025 25

National Customer Service Facsimile:

1300 2025 56

International Enquiries

International Sales and Marketing

Telephone +61 8 8269 0587
Facsimile +61 8 8340 7350
E-Mail export@clipsal.com.au

New Zealand

Clipsal Industries (NZ) Ltd
Telephone +64 9 576 3403

Malaysia

Clipsal Integrated Systems (M) Sdn Bhd
Telephone +60 3 7665 3555

Singapore

Clipsal Integrated Systems Pte Ltd
Telephone +65 6415 3232/3233

China

Clipsal China Limited
Telephone +86 755 8237 5959

Greece

Schneider Electric AE
Telephone +30 69 4646 3200

Hong Kong

Clipsal Integrated Systems (HK) Limited
Telephone +852 2487 0261

India

Schneider Electric India Pvt Ltd
Telephone +91 11 5159 0000

Indonesia

PT Clipsal Graha Nusa
Telephone +62 21 630 6430

Korea

Clipsal Korea Co. Ltd
Telephone +82 549 5550

Pakistan

Clipsal Pakistan (Pvt) Ltd
Telephone +92 21 506 7278

Philippines

Clipsal Philippines Inc.
Telephone +632 683 0275-78

South Africa

Clipsal South Africa (Pty) Ltd
Telephone +27 11 314 5200

Taiwan

Clipsal (Taiwan) Co Ltd
Telephone +886 2 2558 3456

Thailand

Clipsal Thailand Ltd
Telephone +66 2 952 5338-42

United Arab Emirates

Clipsal Middle East
Telephone +971 6 5570 777

United Kingdom

Clipsal Integrated Systems
C/o Schneider Electric
Telephone +44 870 608 8 608

Vietnam

Clipsal - VTEC
Telephone +848 856 3002



Clipsal Australia Pty Ltd reserves the right to change specifications, modify designs and discontinue items without incurring obligation and whilst every effort is made to ensure that descriptions, specifications and other information in this catalogue are correct, no warranty is given in respect thereof and the company shall not be liable for any error therein.

© Clipsal Australia Pty Ltd.

The identified trademarks and copyrights are the property of Clipsal Australia Pty Ltd unless otherwise noted.