



5100T Series

The C-Bus® Telephone Interface Unit allows control and monitoring for a Clipsal C-Bus system via a telephone dial-in and dial-out facility. An audio output is also included, allowing C-Bus® events to be audibly announced via any standard Audio Amplifier. The C-Bus® Telephone Interface connects to either The Public Switched Telephone Network or to a local PABX.

The C-Bus® Telephone Interface Unit includes the facility to issue voice prompts, send commands, report C-Bus® status and to obtain operator responses using DTMF tones. The operator responses are turned into actions on a C-Bus® Network. The C-Bus® Telephone Interface permits control of any pre-programmed C-Bus® Application and Group Address (on, off or ramp to level).

For added security, the C-Bus® Telephone Interface requires the telephone user to enter a user profile number and password to access the voice prompt menus. Upon receipt of the correct password, the C-Bus® Telephone Interface activates a voice prompt menu and directs the user to available actions or more menus.

Any touch-tone phone can be used to access the unit, including house telephones, by dialling a special access code that causes exchange tones to be muted when active.

The C-Bus® Telephone Interface operates in either “Home” or “Away” mode. The mode of use can be determined by a C-Bus® message. The number of rings before the C-Bus® Telephone Interface picks up the line is programmable separately for “Home” and “Away” modes.

The unit allows a data connection to be made using a standard remote modem connected to a PC. This data connection mode allows existing C-Bus® installation software to be used for remote changes to a C-Bus® installation.

The C-Bus Telephone Interface incorporates a history log, is supplied pre-loaded with a standard library of words and phrases, and supports multiple languages.

The Telephone Interface is programmed using a PC running the C-Bus® Telephone Interface configuration software under Microsoft Windows™.

clipsal.com/cis

5100T Series C-Bus® Telephone Interface

- Offers a dial-in and dial-out facility to control and monitor a Clipsal C-Bus® system
- Includes an audio output, so C-Bus® events can be audibly announced
- Data connection mode allows existing C-Bus® installation software to be used for remote changes to a C-Bus® installation
- Programmed via a PC running the C-Bus® Telephone Interface configuration software
- Issue voice prompts, report C-Bus® status, and allows and operator to send commands and set options using standard telephone DTMF tones
- Power from a 12Vdc (polarity independent) or 12Vac (50 or 60 Hz) plug pack
- Connects to either The Public Switched Telephone Network (PSTN) or A Private Automatic Branch Exchange (PABX)
- Includes three RJ12 sockets for telephone connections, designated "Phone In", "Primary Phone Out" and "Secondary Phone Out"
- Connects to a PC via an RS-232 link, using a DB9 connector located on the front face of the unit
- Includes a software selectable C-Bus® network burden and clock
- Supports communication over multiple networks through C-Bus® network bridges
- Operates in "Home" or "Away" modes, and determines operation in these modes in response to a C-Bus® message
- Permits dial-in or local telephone control of any pre-programmed C-Bus® Application and Group Address (on, off or ramp to level)
- The number of rings before line pick up is programmable, separately, for "Home" and "Away" modes
- Includes a user profile number and password to access the voice prompt menus
- Able to dial-out or announce in response to a programmed set of C-Bus® messages
- Incorporates LED indicators for C-Bus® network status, internal communication, RS-232 communications and telephone "Line Grab"
- Incorporates a history log, which records details of incoming and outgoing calls
- Pre-loaded with a standard library of words and phrases
- Supports multiple languages
- Dimensions: H=146.5mm, W=145mm, D=30mm
- Optional mounting bracket allows unit to be mounted directly into Clipsal StarServe Home Networking Unit.

Product of Clipsal Australia Pty. Ltd.

A member of the Schneider Electric Group.

Head Office

12 Park Terrace, Bowden
South Australia 5007
PO Box 103 Hindmarsh
South Australia 5007

Telephone +61 8 8345 9500
Facsimile +61 8 8346 0845
Internet www.clipsal.com/cis
E-Mail cis@clipsal.com.au

CIS Technical Support Hotline:

1300 722 247

Customer Service Enquiries:

1300 2025 25

National Customer Service Facsimile:

1300 2025 56

International Enquiries

International Sales and Marketing

Telephone +61 8 8269 0587
Facsimile +61 8 8340 7350
E-Mail export@clipsal.com.au

New Zealand

Clipsal Industries (NZ) Ltd
Telephone +64 9 576 3403

Malaysia

Clipsal Integrated Systems (M) Sdn Bhd
Telephone +60 3 7665 3555

Singapore

Clipsal Integrated Systems Pte Ltd
Telephone +65 6415 3232/3233

China

Clipsal China Limited
Telephone +86 755 8237 5959

Greece

Schneider Electric AE
Telephone +30 69 4646 3200

Hong Kong

Clipsal Integrated Systems (HK) Limited
Telephone +852 2487 0261

India

Schneider Electric India Pvt Ltd
Telephone +91 11 5159 0000

Indonesia

PT Clipsal Graha Nusa
Telephone +62 21 630 6430

Korea

Clipsal Korea Co. Ltd
Telephone +82 549 5550

Pakistan

Clipsal Pakistan (Pvt) Ltd
Telephone +92 21 506 7278

Philippines

Clipsal Philippines Inc.
Telephone +632 683 0275-78

South Africa

Clipsal South Africa (Pty) Ltd
Telephone +27 11 314 5200

Taiwan

Clipsal (Taiwan) Co Ltd
Telephone +886 2 2558 3456

Thailand

Clipsal Thailand Ltd
Telephone +66 2 952 5338-42

United Arab Emirates

Clipsal Middle East
Telephone +971 6 5570 777

United Kingdom

Clipsal Integrated Systems
C/o Schneider Electric
Telephone +44 870 608 8 608

Vietnam

Clipsal - VTEC
Telephone +848 856 3002



Clipsal Australia Pty Ltd reserves the right to change specifications, modify designs and discontinue items without incurring obligation and whilst every effort is made to ensure that descriptions, specifications and other information in this catalogue are correct, no warranty is given in respect thereof and the company shall not be liable for any error therein.

© Clipsal Australia Pty Ltd.

The identified trademarks and copyrights are the property of Clipsal Australia Pty Ltd unless otherwise noted.