## Clipsal Iconic™ Electronic Mechanisms – Selection Chart





















Model if 41EPBCLM-WW 41EPBM-WW 42E30RLD2M-WW 42E30RLD2M-WW 41E300PBLD2M-WW 41E											
2-Wire 3-Wire Active, neutral 3-Wire 3-Wire 3-Wire 3-Wire 2-Wire 2-Wire 2-Wire 2-Wire 2-Wire 3-Wire	Product Name	Remote mech	Remote	Dimmer	Dimmer	w CTL	w CTL	w CTL	1.5Å USB	3.1A USB	PIR Motion Sensor 3-Wire
Notarial Control Link	Model #	41EPBCLM-VW	41EPBM-VW	42E350RLD2M-VW	42E350RUD2M-VW	41E300PBUD2SM-VW	41E350PBES2SM-VW	41E350PBT2SM-VW	40E1USBM-VW	40E2USBM-VW	41EPIRM-TN
Multiway control  Configurable LED indicator  YES  NO  NO  NO  NO  YES  YES  YES  NA  NA  NA  LED present but configurable LED indicator  YES  NO  NO  NO  NO  YES  YES  YES  NA  NA  NA  NA  LED present but configurable min brightness  NA  NA  NA  NA  NA  NA  NA  NA  NA	2-Wire/ 3-Wire		2-Wire	2-Wire	2-Wire	2-Wire	2-Wire	2-Wire	Active, neutral	Active, neutral	3-Wire
Configurable His Indicator  TES  NO  NO  NO  NO  TES  TES  TES  NA  NA  NA  NA  NA  NA  NA  NA  NA  N	Multiway control					Multiway dimming	Multiway switching		NA	NA	Can parallel multiple devices
Min load  NA  NA  NA  1W  1W  10W  10W  10W  NA  NA  NA  NA  NA  NA  NA  NA  NA  N	Configurable LED indicator	YES	NO	NO	NO	YES	YES	YES	NA	NA	LED present but not configurable
Max load  ControlLink communication only, no direct load control  NA  NA  NA  NA  NA  NA  NA  NA  NA  N	Configurable min brightness	NA	NA	YES	YES	YES	NA	NA	NA	NA	NA
Max load communication only, no direct load control 240V 50mA 350W 350W 350W 350W 350W 350W 1.5A 2.1A per port (3.1A max) 750W, 150W LE M3(0.5A @0.5p M3(0.5p M3(0	Min load	NA	NA	1W	1W	10W	10W	10W	NA	NA	NA
Built-in over-temp, overload, short circuit protection  NA  Overload  YES  YES  YES  YES  YES  YES  YES  Overtemp  Overtemp  Overload, short circuit protection  NA  NO  NO  NO  NO  NO  NO  NO  NO  NO	Max load	communication only,	240V 50mA	350W	350W	300W	350W	350W	1.5A		750W, 150W LED, M3(0.5A @0.5pf)
Suitable for fan motors  NA  NO  NO  NO  NO  NO  NO  NO  NO  NO	Timer range	NA	NA	NA	NA	NA	Infinite	30s- 4hr	NA	NA	10s - 15min
Depth from grid Compatible wall box 39mm standard 55mm deep 41mm standard 55mm standar		NA	Overload	YES	YES	YES	YES	YES	YES	YES	Overtemp
Compatible wall box standard deep standard  No. of units in a plate 6 6 3 (de-rating applies) 6 (de-rating applies) 6 (de-rating applies) 3 2 2 3  Application Provides multiway control with matching LED Provides multiway control ma	Suitable for fan motors	NA	NO	NO	YES	NO	NO	NO	NA	NA	YES
Application Provides multiway control with multiway control halogen, incandescent incandescent matching LED.  Provides multiway Provides Lighting – LED, halogen, incandescent											
control with multiway control halogen, maltimay control halogen, matching LED halogen, multiway control halogen, incandescent incandesc	No. of units in a plate	6	6	3 (de-rating applies)	3 (de-rating applies)	6 (de-rating applies)	6 (de-rating applies)	6 (de-rating applies)	3	2	3
	Application	control with matching LED		halogen,	halogen, small fans,	LED, halogen,	LED, halogen,	LED, halogen,			pantry, W.I.R, entry,

clipsal.com/iconic



## Clipsal Iconic™ BLE Mechanism – Selection Chart















Product Name	Smart PB Remote mech with LED	PB Switch 6A w BLE 3-Wire	PB Timer 6A w BLE 3-Wire	PB Timer 10A w BLE 3-Wire	PB Time Clock 6A w BLE 3-Wire	PB Time Clock 10A w BLE 3-Wire	PB Wiser Dimmer 300W w BLE 3-Wire
Model #	41EPBCLM-VW	41E6PBES3SBM-VW	41E6PBT3SBM-VW	41E10PBT3SBM-VW	41E6PBTC3SBM-VW	41E10PBTC3SBM-VW	41EPBDWCLM-VW
2-Wire/ 3-Wire	3-Wire (Active, Neutral, ControlLink)	3-Wire	3-Wire	3-Wire	3-Wire	3-Wire	3-Wire
Multiway control	Slave / Remote Control	Multiway switching	Multiway remote trigger	Multiway remote trigger	Multiway remote trigger	Multiway remote trigger	Multiway dimming
Smart device app configuration	NO	YES	YES	YES	YES	YES	YES
Configurable LED indicator	YES	YES	YES	YES	YES	YES	YES
Configurable min brightness	NA	NA	NA	NA	NA	NA	YES
Min load	NA	NA	NA	NA	NA	NA	NA
Max load	ControlLink communication only, no direct load control	6AX/1440W 6A @ 0.8pf M30 (5A @ 0.5pf)	6AX/1440W 6A @ 0.8pf M30 (5A @ 0.5pf)	10AX/15A Res 10A @ 0.8pf M40 (6A @ 0.5pf)	6AX/1440W 6A @ 0.8pf M30 (5A @ 0.5pf)	10AX/15A Res 10A @ 0.8pf M40 (6A @ 0.5pf)	300W
Timer range	NA	Infinite	1s-24hr	1s-24hr	1s-24hr	1s-24hr	1s-24hr
24hr / 7day schedule function	NA	NO	NO	NO	YES	YES	YES (with selectable dimming levels)
Built-in over-temp, overload, short circuit protection	NA	Overtemp	Overtemp	Overtemp	Overtemp	Overtemp	YES
Suitable for fan motors	NA	YES	YES	YES	YES	YES	NO
Depth from grid Compatible wall box	39mm Standard	39mm standard	39mm standard	70mm deep	39mm standard	70mm deep	70mm deep
No. of units in a plate	6	6 (de-rating applies)	6 (de-rating applies)	3 (de-rating applies)	6 (de-rating applies)	3 (de-rating applies)	3 (de-rating applies)
Application	Provides multiway control with matching LED indicator.	All lighting, exhaust fans, contactors, sensors	All lighting, exhaust fans, garden lights, pumps, decorative lights	All lighting, exhaust fans, outdoor heater, pumps, garden lights	All lighting, exhaust fans, pumps, garden lights, heated towel rail	All lighting, exhaust fans, pool pump, HWS booster, garden lights	LED, halogen, incandes bedrooms, lounge, dinir family

clipsal.com/iconic

